



NOTES

- POSTS AND RAILS TO BE FIRST GRADE PRESSURE TREATED TIMBER FREE FROM WARPS AND TWISTS AND STRAIGHT TO WITHIN STATED TOLERANCES. (>± 2.0mm/METRE)
- COMPLETED TIMBER STRUCTURE AND GROUNDWORKS POSITIONING OF POSTS TO BE WITHIN ± 5mm OF TRUE POSITION IN ALL ASPECTS.
- GROUND ANCHORS AND REAR STAYS MAY BE REQUIRED IN CERTAIN CIRCUMSTANCES SUBJECT TO GROUND AND SITE CONDITIONS. IF FOUND NECESSARY THIS WORK WOULD BEST BE CARRIED OUT AFTER STANDARD INSTALLATION.
- TOP SURFACE OF LOWER RAIL IS BASIC DATUM FOR MIRROR ALIGNMENT

PORTRAIT INSTALLATION REQUIREMENTS

DRAWN COLIN SPOONER		CONCORDE GLASS CONCORDE GLASS LTD - LINX HOUSE - GOLF ROAD INDUSTRIAL ESTATE - ENTERPRISE ROAD MABLETHORPE - LINCOLNSHIRE - LN12 1NB TEL. 01507 472600	
CHECKED			
REV. A DIM. 2362.00 WAS 2269.00. MOUNT DIMENSION (2318.00) ADDED.		TITLE POST AND RAIL INSTALLATION DETAILS FOR LANDSCAPE MIRROR INSTALLATION	
		MATERIAL FIRST GRADE PRESSURE TREATED TIMBER	
SIZE A4		DWG NO EQM1001-015	REV A
SCALE 0.25			SHEET 1 OF 1

This drawing and all information contained therein is the property of © CONCORDE GLASS LTD and must not be copied or reproduced without prior permission

dimensions in millimetres - unspecified tolerances :-	general machined finish N7 remove burrs and sharp edges threads to be medium fit metric 6H.6g
0 = ± 0.5 0.0 = ± 0.25 0.00 = ± 0.01	