



(\* ) DIMENSIONS SHOWN FOR STANDARD MIRROR HEIGHT  
 COULD BE VARIED BY CUSTOMER CHOICE

NOTES

- POSTS AND RAILS TO BE PREFABRICATED FROM STANDARD ROLLED STEEL SECTIONS AS DETAILED. PARTS TO BE TRUE AND STRAIGHT AND FREE OF DAMAGE OR DISTORSION.
- COMPLETED STRUCTURE AND GROUNDWORKS POSITIONING OF POSTS TO BE WITHIN  $\pm 5$ mm OF TRUE POSITION IN ALL ASPECTS.
- PARTS TO TO PRE-TREATED WITH GOOD QUALITY ANTI-RUST COATING AND FINISH PAINTED AFTER ASSEMBLY.
- GROUND ANCHORS AND REAR STAYS MAY BE REQUIRED IN CERTAIN CIRCUMSTANCES SUBJECT TO GROUND AND SITE CONDITIONS. IF FOUND NECESSARY THIS WORK WOULD BEST BE CARRIED OUT AFTER STANDARD INSTALLATION.
- TOP SURFACE OF LOWER RAIL IS BASIC DATUM FOR MIRROR ALIGNMENT

**PORTRAIT INSTALLATION REQUIREMENTS - METAL POSTS AND RAILS.**

This drawing and all information contained therein is the property of © CONCORDE GLASS LTD and must not be copied or reproduced without prior permission

dimensions in millimetres - unspecified tolerances :-  
 0 =  $\pm 0.5$     0.0 =  $\pm 0.25$     0.00 =  $\pm 0.01$

general machined finish N7  
 remove burrs and sharp edges  
 threads to be medium fit metric 6H.6g

DRAWN COLIN SPOONER		<b>CONCORDE GLASS</b>	
CHECKED			
		CONCORDE GLASS LTD - LINX HOUSE - GOLF ROAD INDUSTRIAL ESTATE - ENTERPRISE ROAD MABLETHORPE - LINCOLNSHIRE - LN12 1NB TEL. 01507 472600	
		TITLE POST AND RAIL INSTALLATION DETAILS FOR PORTRAIT MIRROR ISTALLATION	
REV A - DIM. 2362.00 WAS 2269.00. MIRROR MOUNT DIMENSION (2318.00) ADDED		MATERIAL STANDARD ROLLED STEEL SECTIONS	
SIZE A4	DWG NO EM1005-015	REV A	
SCALE .025	SHEET 1 OF 1		