



NOTES

- POSTS AND RAILS TO BE PREFABRICATED FROM STANDARD ROLLED STEEL SECTIONS AS DETAILED. PARTS TO BE TRUE AND STRAIGHT AND FREE OF DAMAGE OR DISTORSION.
- COMPLETED STRUCTURE AND GROUNDWORKS POSITIONING OF POSTS TO BE WITHIN ±5mm OF TRUE POSITION IN ALL ASPECTS.
- PARTS TO TO PRE-TREATED WITH GOOD QUALITY ANTI-RUST COATING AND FINISH PAINTED AFTER ASSEMBLY.
- GROUND ANCHORS AND REAR STAYS MAY BE REQUIRED IN CERTAIN CIRCUMSTANCES SUBJECT TO GROUND AND SITE CONDITIONS. IF FOUND NECESSARY THIS WORK WOULD BEST BE CARRIED OUT AFTER STANDARD INSTALLATION.
- TOP SURFACE OF LOWER RAIL IS BASIC DATUM FOR MIRROR ALIGNMENT

This drawing and all information contained therein is the property of © CONCORDE GLASS LTD and must not be copied or reproduced without prior permission

dimensions in millimetres - unspecified tolerances :- general machined finish N7  
 0 = ± 0.5    0.0 = ± 0.25    0.00 = ± 0.01    remove burrs and sharp edges  
 threads to be medium fit metric 6H.6g

**LANDSCAPE INSTALLATION REQUIREMENTS - METAL POSTS AND RAILS.**

DRAWN COLIN SPOONER		<b>CONCORDE GLASS</b>	
CHECKED			
		CONCORDE GLASS LTD - LINX HOUSE - GOLF ROAD INDUSTRIAL ESTATE - ENTERPRISE ROAD MABLETHORPE - LINCOLNSHIRE - LN12 1NB TEL. 01507 472600	
		TITLE POST AND RAIL INSTALLATION DETAILS FOR LANDSCAPE MIRROR INSTALLATION	
		MATERIAL STANDARD ROLLED STEEL SECTIONS	
SIZE A4		DWG NO EQM1003-015	REV
SCALE .025		SHEET 1 OF 1	